



## 37.2 Ton Standard Bulldozer

# T-REX238-8

The Revaro T-REX2372 is a powerful 37.2-ton heavy-duty crawler bulldozer built for demanding earthmoving, mining, and large-scale construction operations. Powered by a robust 257 kW engine, it delivers exceptional pushing power, reliable performance, and efficient fuel consumption in tough working environments. With a maximum traction force of 281 kN, a durable undercarriage, and multiple blade options including straight-tilt, angle, U, and semi-U blades with capacities up to 16.2 m<sup>3</sup>, the T-REX2372 is designed to move large volumes of material efficiently. Its strong frame, advanced cooling system, and comfortable operator station ensure durability, productivity, and dependable performance during continuous heavy-duty operation.



### Specs

| General Specs                  |                               |
|--------------------------------|-------------------------------|
| Dimensions                     | 6535×4150×3515mm              |
| Weight                         | 37200kg                       |
| Engine model                   | QSNT-C345S31 / NTA855-C360S10 |
| Power                          | 257kW / 2000r/min             |
| Fuel consumption               | 222-28 / 29-38L/H             |
| Ground contact length          | 3150mm                        |
| Ground specific pressure       | 0.105MPa                      |
| Minimum ground clearance       | 500mm                         |
| Gradeability                   | 30°                           |
| No. of track shoes (each side) | 41                            |
| Width of Track shoe            | 560mm                         |
| Track Gauge                    | 2140mm                        |
| pitch                          | 228.6mm                       |



|                                                |                               |
|------------------------------------------------|-------------------------------|
| No of carrier rollers (each side)              | 2                             |
| No. of Track roller (each side)                | 7                             |
| Maximum traction force                         | 281KN                         |
| Straight-tilt Blade (Capacity & inclination)   | 4150×1592mm (10m³ & 1000mm)   |
| Angle Blade (Capacity & inclination)           | 5000×1142mm (6.2m³ & 500mm)   |
| U Blade (Capacity & inclination)               | 4440×1740 mm(16.2m³ & 1000mm) |
| Semi-U-Blade (Capacity & inclination)          | 4150×1712 mm(11.7m³ & 1000mm) |
| Blade lift height (Straight, Angle, U, Semi-U) | 1560/1703/1560/1560mm         |
| Blade depth (Straight, Angle, U, Semi-U)       | 560/630/560/560mm             |
| Max Forward Speed - F1, F2, F3                 | 3.6, 6.6, 11.5km/h            |
| Max Reverse Speed - R1, R2, R3                 | 4.4, 7.8, 13.5km/h            |
| Coolant capacity                               | 121L                          |
| Fuel tank capacity                             | 640L                          |
| Engine oil capacity                            | 47L                           |

